

**FullHD**  
1920x1080**ONVIF**

## AiS-I23S-S, 2MP Dome Camera

2MP IP Camera with fixed, 2.8 mm lens

The **AiS-I23S-S** is 2MP IP CCTV Camera for Video Surveillance systems. This camera has **2.8 mm** lenses and **30 m** distance Infrared LED light to record high quality video even in low-light areas.

It can be installed Outdoor and Indoor as it has (**IP67**) weatherproof protective housing for day and night video surveillance. In order to connect with NVRs, this 2MP CCTV camera needs the Coaxial cable, which is applied in IP Surveillance systems. Acumen provides 3 years of a manufacturer warranty and free online technical support from Taiwan for this model.

- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor;
- IP CCTV Camera;
- Lenses: fixed, 2.8 mm;
- Maximum IR distance: 30 m;
- Weatherproof: IP67;
- WDR, Internal PoE, SD Card.

## SPECIFICATION FOR AiS-I23S-S

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Minimum Illumination	Color mode: 0.01 LUX at (F1.2, AGC ON), 0 LUX with IR; Black & White: 0.001 LUX at (F1.2, AGC ON), 0 LUX with IR.
Image Resolution	2MP
Video	1080P at 30fps
TV System	PAL / NTSC
Video Delay	0.3 seconds within the LAN
Shutter Speed	from 1/25s to 1/50.000s, from 1/30s to 1/60.000s
Video Compression	H.265/H.265+
Lens Type	fixed, 2.8 mm
Infrared LEDs	18 pcs
Infrared Distance	30 m
Day / Night Mode	Color/ Black and White (IR-CUT)
Ethernet	RJ45 (10/100 Base-T)
S/N Ratio	>50dB
Scanning System	Progressive Scan
Recording Mode	NVR / NAS / CMS / Web
Motion Detection	Yes
Defog Mode	Yes
Corridor Pattern	Yes
Additionally	WDR, Internal PoE, SD Card
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF Version	2.4
Browsers	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phones	iPhone, iPad, Android, Android Pad
Menu Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Dutch
Image Configuration	Saturation, Brightness, Contrast, Sharpness, Mirror, White Balance, Flicker Control
Weatherproof	IP67

Operating Temperature	-65°C to +65°C
Power Source	12V DC
Dimensions	Ø94 x 69 mm
Weight	400 g

