

AI GAX-1006

Professional 6 channel audio power sequencer controller sound system for church with LED Display



SPECIFICATIONS

Product Model	AI GAX-1006
Power	5000W/6000W
Product name	6 channel audio power sequencer controller sound system for church
Channel	6 Channel
Screen	LED Screen
Power requirement	AC 170 - 265V
Output relay contact current	C90 - 260V / 50 - 60Hz
Material	Metal

Panel Description

- ▶ Panel Color: Iron Black
- ▶ Power input conditions (single-phase 3-wire): AC90-260V 50-60HZ two-phase (three-wire: zero, fire, ground)
- ▶ Channel quantity: 6-way universal socket relay controlled output
- ▶ Relay controlled output maximum withstand single power/total power (reactive power): 5000W/6000W maximum withstand reactive power
- ▶ Output power socket specifications: flame retardant ABS material, can withstand a maximum current of 13A, brass material, standard universal socket
- ▶ Features: 1. Turn on in sequence and turn off in reverse order 2. Accurate voltage display
- ▶ Interval time/timing time of each switch: 1 second
- ▶ Output relay contact current: 30A 277VAC
- ▶ Specifications of circuit board: double-sided fiberboard, secondary thickening and thickening of main power wiring
- ▶ Power supply specifications: built-in switching power supply, suitable for global voltage AC90-260V 50-60HZ
- ▶ Main cable specification: 3*2.5 square cable, the total length is 1.5 meters with 3C plug
- ▶ Open type: square boat switch
- ▶ Function display Voltage display meter type: red digital tube display voltage meter

- ▶ Stacker cascading function: none
- ▶ Body size: length 482MM * width 58MM * height 44MM (non-standard 1U)
- ▶ Single machine packaging size: length 530MM * width 80MM * height 90MM (American cattle carton) Gross weight: 1.6KG
- ▶ The weight of the whole piece and the size of the outer packaging: 1 piece and 5 sets of 10KG in total, the outer packaging size: length 550*width 100*height 420mm"

Panel Description



DIMENSIONS

